

# GOOSENECK MICROPHONES

## BENEFITS


- Rugged
- Various lengths and cross-sections of gooseneck
- Easy integration including onboard mounting
- Excellent acoustic quality
- Waterproof anti-vandal version

## APPLICATIONS

The range of gooseneck microphones meets all communication requirements including in severe environments:



- **TRANSPORT:** Buses - Rail - Marine
- **SECURITY:** Air traffic control - Counter intercom
- **INDUSTRY**
- **TELECOMMUNICATIONS:** Conference halls - Radio applications



In addition to standard products **LEM** is able to develop specific equipment in term of design and acoustic.



# GOOSENECK MICROPHONES

## FEATURES

	 DU 112	 EU 822
	<b>Vibration resistant</b> Radio - Public Address - Intercom - Telecommunication	<b>Intensive use</b> Intercom - Telecommunications - Public Address
<b>Microphone</b>	dynamic	electret
<b>Directivity</b>	unidirectionnal	unidirectionnal
<b>Efficiency</b>	1,9 mV/Pa 150 mV/Pa 775 mV/Pa	8,8 mV/Pa
<b>Gooseneck diameter</b>	8 to 15 mm	8 to 15 mm
<b>Gooseneck length</b>	250 to 600 mm	200 to 500 mm
<b>Mounting/Remark</b>	M10 nut or XLR plug Isolated shield (option)	M10 nut or XLR plug Illuminated ring (option)

	 EU 1000	 ED 400
	<b>Esthetic</b> Gooseneck and steel tube Conference halls	<b>Waterproof</b> Corrosion resistant Motorcycles - Ships
<b>Microphone</b>	electret	electret
<b>Directivity</b>	unidirectionnal	differential
<b>Efficiency</b>	8,8 mV/Pa	410 mV/Pa
<b>Gooseneck diameter</b>	6 mm	10 mm coated
<b>Gooseneck length</b>	250 to 400 mm	250 mm
<b>Mounting*/Remark</b>	M10 nut or XLR or DIN plug	M10 nut

\* others on demand

## ACCESSORIES - Desk mounting



DU112 and EU1000 can be mounted on call station desk. Following functions are available:

- Electret cardioïde microphone
- Compressor - limiter - audio expander
- PTT
- Loudspeakers
- 0,5W amplifier
- Volume control
- Headset output jack and switch off speakers
- Power supply cord

Gooseneck length: 250 mm

Dimensions LxPxH: 140x125x50

Weight: 520g